

## TECHNICAL DATA

<b>Description of commodity: GLP047 Frontlit PET with grey back 420gsm</b>			
<b>ITEM</b>	<b>DATA</b>	<b>UNIT</b>	<b>TEST METHOD</b>
<b>Fabric</b>	NO		DIN EN ISO2060
<b>Construction</b>		inch	DIN60001
<b>Total weight</b>	420	g/sq.m	DIN53352 BS3424 method5A
<b>Weight of PET</b>	130	g/sq.m	DIN53352 BS3424 method5B
<b>Weight of PVC</b>	290	g/sq.m	DIN53352 BS3424 method5B
<b>Tensile strength</b>	Warp: 1280	N/5cm	DIN53354 BS3424 method6A
	Weft: 1130		
<b>Tearing strength</b>	Warp: 200	N	DIN53356 BS3424 method 7A
	Weft: 170		
<b>Adhesion</b>	60	N/5cm	DIN53357 BS3425 method9B
<b>Suitable temperature</b>	-20 -----+70	°C	DIN 53372 BS3424 method10
<b>Flame retardancy</b>	As requested.		
<b>Printer type:</b>	Printable with VUTEK, SCITEX, NUR, DGI, MIMAKI, ROLAND, MUTOH, SEIKO, JET-I and etc		

**The indexes above are on average, so there will be ±5% tolerance for actual material.**