

Type : SS-3

Removable Self Adhesive Vinyl Technical Information

Specification	Description	
PVC	Type	Calendered polymeric soft PVC film
	Thickness	80 ± 10um
	Color Code	Ceramic white
	Shrinkage	0.6%
	Surface Tension	≧ 30dn/cm
	Opacity	>95%
Adhesive	Type	Gray solvent based removable pressure sensitive glue
	Weight(g/ m ²)	25 ± 5
	Adhesion Temperature	15°C ~ 40°C
	180° Peeling Force	≧ 12N/25mm 24H
	Initial Adhesion-Loop Tack	≧ 5N/25mm*25mm
	Holding Power	≧ 3000min
	Removable Durability	One year cleanly removable glue on clean glass, Bakeable paint, stainless surface at temperature of 23-25 C and RH of 50-60%
Liner	Type	Double side polycoated kraft paper
	Color	white
	Weight	140g ± 10g/ m ²
	Release Force	0.05~0.2N/25mm
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	

Application	Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application.
Compatibility of printers and ink	Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek and HP Scitex. Inks should be the original ink from the printer manufacturers. The best printing temperature is 35-40°C.