

Super Floor Sticker Aluminium(R11)-1

-----Technical Data Sheet -----

- Code No.:** TFL-01
- Description:** Premium quality aluminum surface with coating of strong slip-resistance(R11 grade). Offered with a liner of double-side PE-coated paper.
- Surface:** 215±20um aluminum surface with coating of slip-resistance.
- Adhesive:** 50±5um transparent adhesive-permanent.
- Liner:** 135±5gsm double-side PE-coated white wood-pulp paper.
- Durability:** Outdoor 3 months to 6months, depends on the environment.
- Compatible Ink:** Eco Solvent Ink/ HP Latex Inks
- Features:** With aluminum surface, **TFL-01** has low inflammability and compare with PVC vinyl, it won't shrink and won't turn to yellowish after being applied without man-made damage. The special coating surface makes **TFL-01** have strong anti-resistance.
- Applications:** Widely used for wall and floor advertisement, can be applied to any rugged and rough surfaces such as asphalt, concrete and paving stones.
- Size Available:** 1370MM *10 M
- Physical Characteristics:**

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.215MM ± 0.020MM
Adhesive Thickness	ZC/QR08	0.050MM ± 0.005MM
Liner Thickness	ZC/QR08	0.140MM ± 0.010MM
Surface brightness	ZC/QR08	Approx. 24GS
	Tested by D60 standard	
Adhesive Force	ZC/QR08 20min on SS	2.0kg/inch 18%
Release Force	ZC/QR08	0.045±0.005 kg/inch
Initial Tack	20Minutes in the standard lab	≤ Ball No.5
Test Temperature		25±2℃, 65%±15% RH
Application Temperature		10℃-35℃ 30%-70% RH
Storage Temperature		10℃-35℃ 30%-70% RH