

WHITE FLOOR STICKER

-----Technical Data Sheet -----

Code No.: TFL-03
Description: Premium quality white sandblast matte PVC surface with a liner of single side PE-coated paper.
Surface: 200±10um white sandblast matte PVC film.
Adhesive: 30±3um transparent adhesive-permanent.
Liner: 100±5gsm single side PE-coated release paper.
Durability: Indoor use up to 1 year.

Compatible Ink: UV Ink/ Eco Solvent Ink/ HP Latex Inks

Features: With sandblast matte PVC, **TFL-03** has better slip resistance(R10 grade) than other glossy PVC floor sticker.

Applications: Widely used for floor graphics.

Size: 1.27 * 50M

Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.200MM ± 0.010MM
Adhesive Thickness	ZC/QR08	0.030MM ± 0.003MM
Liner Thickness	ZC/QR08	0.120MM ± 0.010MM
Surface brightness	ZC/QR08	Approx. 3.2 GS
	Tested by D60 standard Photometric apparatus;	
Adhesive Force	ZC/QR08	1.1kg/inch± 18%
Release Force	ZC/QR08	Approx. 0.015kg/inch
Initial Tack	20Minutes in the standard lab	Ball No.9
Test Temperature		25±2℃, 65%±15%RH
Application Temperature		+10℃ to +60℃
Storage Temperature		+25℃ to +28℃