

CT-1

Description: Transparent PET lamination film with clear adhesive. Offered with a liner of PET release film.

Surface: 55±5um monomeric transparent PET film.

Adhesive: 30±3um clear adhesive-permanent.

Liner: 25±5um PET release film.

Warranty: 1 year after production.

Features: With special finish of PET film surface, L-2142 can be laminated to any white vinyls and be pasted to a clean and smooth wall or glass to make it be a white board, it can be written by white board maker pen and the writing can be removed easily.

Applications: Widely used for lamination on PVC sticker, glass, acrylic, wall as writing board.

Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.055MM ± 0.005MM
Adhesive Thickness	ZC/QR08	0.030MM ± 0.003MM
Liner Thickness	ZC/QR08	0.025MM ± 0.005MM
Surface brightness	ZC/QR08 Tested by D60 standard Photometric apparatus;	166±5GS
Adhesive Force	ZC/QR08	1.10kg± 18%
Release Force	ZC/QR08	Approx. 7g
Initial Tack	20Minutes in the standard lab	Ball No.5
Test Temperature		25±2℃, 65%±15%RH
Application Temperature		10℃-35℃ 30%-70%RH
Storage Temperature		10℃-35℃ 30%-70%RH