

CW-1

- Description:** Finished with colorful PET, it shows different colors under different rays.
- Surface:** $58 \pm 3\mu\text{m}$ special colorful shining PET with 1.5H Scratch-resistant
- Adhesive:** $18 \pm 3\mu\text{m}$ transparent adhesive-removable.
- Liner:** $25 \pm 3\mu\text{m}$ PET release liner.
- Warranty:** 1 year after production.

Compatible Ink: UV Ink.

Features: With dichroic PET film, L-9301 has a special shining effect and it changes color when view from different angles or from different lights.

Applications: Widely used for any clean and smooth surfaces.

Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness(with coating)	ZC/QR08	0.058MM-0.003MM
Adhesive Thickness	ZC/QR08	0.018MM \pm 0.003MM
Liner Thickness	ZC/QR08	0.025MM \pm 0.003MM
Surface brightness	ZC/QR08	200+GS
Adhesive Force	ZC/QR08	0.23kg \pm 18% /inch
Release Force	ZC/QR08	Approx 2g /inch
Initial Tack	20Minutes in the standard lab	Ball No.3
Test Temperature		$25 \pm 2^\circ\text{C}$, 65% \pm 15%RH
Application Temperature		10°C - 35°C 30%-70%RH
Storage Temperature		10°C - 35°C 30%-70%RH