

GBC-1

- Description:** Premium quality high clear PET film. Transparent PET film with clear adhesive. Offered with a liner of matte PET release film.
- Surface:** 75±5um transparent glossy PVC film.
- Adhesive:** 22±3um clear-removable.
- Liner:** 50±5um matte PET release film.
- Durability:** Outdoor use up to 1 year.
- Compatible Ink:** UV Ink
- Features:** With high clear PET film, I-1303 has super clear effect after being printed with UV ink.
- Applications:** Widely used for storefront window graphics.

Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.075MM ± 0.005MM
Adhesive Thickness	ZC/QR08	0.022MM ± 0.003MM
Liner Thickness	ZC/QR08	0.050MM ± 0.005MM
Transmittance	ZC/QR08 Tested by D60 standard Photometric apparatus;	≥88%
Adhesive Force	ZC/QR08	0.050kg/inch ± 18%
Release Force	ZC/QR08	Approx. 0.005kg/inch
Initial Tack	20Minutes in the standard lab	Ball No.3-5
Test Temperature		25±2°C, 65%±15%RH
Application Temperature		10°C-35°C 30%-70%RH
Storage Temperature		10°C-35°C 30%-70%RH