

SO-7

Specification	Description	
PVC	Type	Calendered polymeric soft PVC film
	Thickness	180 ± 10um
	Color Code	Transparent
	Back	Transparent
	Shrinkage	≤0.6%
	Surface Tension	≥30dn/cm
	Opacity	>99%
	Holes No.	Average 110/sq in
	Hole Diameter	1.50mm
	Distance Between Holes	Left-right 1.25mm Up-down 2.4mm
	Hole Space	30%
Adhesive	Type	Clear solvent based removable pressure sensitive glue
	Weight(g/ m²)	35 ± 5
	Adhesion Temperature	15°C ~ 40°C
	Peeling Force	≥5N/25mm 24H (FTM1)
	Initial Adhesion- Ball Tack	≥3N/25MM*25MM (FTM9)
	Holding Power	≥1440min (FTM8)
	Removable Durability	One year cleanly removable glue on clean glass surface at temperature of 23~25°C and RH of 50~60%
底纸Liner	Type	Laminated OPP Film
	Color	Clear
	Weight	120g ± 10g/ m²
	Release Force	0.05~0.20N/25MM
Storage Period	12 months under ordinary condition at temperature of 10°C-22°C and relative humidity of 50-60%	
Application	One way vision media used in digital and silk screen printing machines for signage display, vehicle graphics, subway and glass walls of building	
Compatibility of machines and ink	Media is suitable for all solvent and eco solvent digital printers with heating system including Phaeton, Infiniti, Mimaki, Roland, Vutek, HP Scitex, UV and Latex. Inks should be the original ink from the printer manufacturers.	