

# W001P FR (Wall Sticker)

## Description

**Basic material:** Contains PVC film and non woven fabric

**Adhesive:** Permanent clear solvent based acrylic adhesive

**Release liner:** One side PE and silicon coated kraft paper, 140gsm

**Width:** 0.914/1.06/1.27/1.37/1.52m

**Length:** 50m

**Shelf Life:** Up to 1 year at 20 °C and relative humidity of 50%

**Durability:** Up to 1 year

Item	Unit	Value	Test Method
Basic material weight	µm	390-420	GB/T6672-2001
finished product weight	µm	590-600	GB/T6672-2001
Adhesive weight	g/m <sup>2</sup>	50-55	FINAT12
Tensile Strength at break MD	N/50 mm	350N	GB/T1040.1-2006
Tensile Strength at Break CD	N/50 mm	250N	GB/T1040.1-2006
Dimensional stability MD	%	0%	FINAT14
Dimensional stability CD	%	0%	FINAT14
Initial Adhesion	N/25mm	/	Finat9
180 Peel - 20 minutes	N/25 mm	10-15	Finat1
180 Peel - 24 hours	N/25 mm	15-18	Finat1

**Applied Printers** Inkjet printing with ECO Solvent , UV and Latex inks

**Conclusions and Announcements**

1. Easy to exhaust, convenient and simple construction.
2. Can replace magnetic stickers, simpler, more convenient, and more cost-effective.
3. Suit to flat and smooth surface. Or borrow another adhesive carrier.