

# TW-185FR

## (Mural Wall Covering)

### Application

Mural, Wall Covering

### Technical Specifications

Base Material	100% Polyester	DIN 60001, ASTM D7641
Yarn	75D*200D	DIN EN 2060, ASTM D1907
Weave Method	Woven	---
Weight	185 ± 20gsm	ISO536
Thickness	590 ± 50 μm	ISO534
Opacity	≥ 80%	ISO2471
Whiteness	70 ± 10	ISO11475
Color	L*: 90.0 ± 2.0; a*: -1.0 ± 2.0; b*: 2.5 ± 2.0	---
Gloss [60° ]	3 ± 2	---
Shrinkage	≤ 5%	200° C, 45s
Flame Resistance	DIN 4102-1 B1, NFPA 701	DIN 4102-1 B1, NFPA 701
Recommend Fixation Temperature	190-200°C, 45s	---
Yellowing Temperature	≥ 210°C	SUPRKC REX-C400, 30s

### Storage Instructions

The product should be stored in the original packaging for protection. It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15° C [59° F] ~ 35° C [95° F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

### Features



### Compatible Inks

