

White Block Backdrop Textile

SPB-305FR



SPECIFICATIONS	IMPERIAL	TEST METHOD
Material	100% polyester	DIN 60001, ASTM D7641
Weight	305g/sq.m, 9.0 oz/sq.yd	ISO536
Yarn	75x55 denier	DIN EN ISO 2060,ASTM D1907
Weave Method	Warp-knitted 2 bar	
Shrinkage	≤3%	200 °C, 45s
Opacity	>99%	ISO2471
Elasticity	Warp:(4±2)% Weft:(2±2)%	Length*Width=200*50mm,- Speed=100mm/min, Tension=20N
Flame Resistance	DIN 4102-1 B1,NFPA 701 ,EN13501-1	DIN 4102-1 B1,NFPA 701 ,EN13501-1
Recommend Fixation Temperature	190-200 °C,45s	
Yellowing Temperature	≥210 °C	SUPRKC REX-C400,30s
Maximum Width	3.2m	DIN EN ISO 3759,ASTM D751-2006
Standard Length	50m	DIN EN ISO 3759,ASTM D751-2006
Compatible Inks	Dye-sub Transfer, UV, Dye-sub Direct, Latex	
Application	Backdrops,Pop-up, Frame, Exhibition,Display systems	