

# GP-800

| ITEM                  | DATA                       | UNIT   | TEST METHOD               |
|-----------------------|----------------------------|--------|---------------------------|
| Fabric                | 100%PES                    |        | DIN EN ISO2060            |
| Construction          | 15%polyester,85%PVC        |        | DIN60001                  |
| Total thickness       | 1700                       | μm     | GB/T6672-2001             |
| Thickness-surface     | 50                         |        |                           |
| Thickness-fabric      | 300                        |        |                           |
| Thickness-foaming     | 1600                       |        |                           |
| Total weight          | 800g                       | g/sq.m | DIN53352 BS3424 method5A  |
| Tensile strength      | Warp: 1200                 | N/5cm  | DIN53354 BS3424 method6A  |
|                       | Weft: 800                  |        |                           |
| Tearing strength      | Warp: 50                   | N      | DIN53356 BS3424 method 7A |
|                       | Weft: 35                   |        |                           |
| Adhesion              | /                          | N/5cm  | DIN53357 BS3425 method9B  |
| Suitable temperature  | -35---+35                  | °C     | DIN 53372 BS3424 method10 |
| Flame retardancy      | B1 Included.               |        |                           |
| Anti Slip             | R11                        |        |                           |
| Compatible ink        | UV                         |        |                           |
| Standard width/length | 1.60m/2.50m/3.20m x 25~30m |        |                           |